

Technical Data Sheet



INTERIOR WALL PRIMER (MARVEL)

PHYSICAL DESCRIPTION

Interior Wall Primer is a water-based wall coating suitable for application on interiors as an undercoat to interior emulsions. It provides

1. Excellent opacity and whiteness
 2. Improves appearance of top coat
 3. Does not chalk and can be applied on adequately cured fresh plaster
 4. Does not require curing with water
 5. Provides excellent adhesion to top coat emulsions
 6. Prevents peeling off of top coat emulsions
-

SPECIFICATION

Colour	As per the requirement
Gloss	Matt
Dilution	Water
Specific Gravity	1.5 +/- 0.03
Touch Dry	30 Minutes
Recoat	After 12 hours
Application	Brush, Roller

PACKING

20 Litres, 4 Litres, 1 Litre

POST APPLICATION INSTRUCTIONS

For the best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth at regular intervals of six months.

SAFETY HEALTH AND ENVIRONMENTAL INFORMATION

- Keep the container tightly closed. Keep it out of the reach of children

- Store in a cool, dry, well-ventilated place away from sources of heat, ignition and direct sunlight
- If swallowed, seek medical advice immediately and show this container or label
- Avoid contact with skin or eyes. Wear suitable gloves as it may cause sensitization by skin contact
- After contact with skin, wash immediately with soap and water or a proprietary skin cleanser. Do not use solvent thinners or white spirits
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- Do not empty into drains. Use only in well ventilated areas
- Ensure good ventilation during application and drying • Do not use empty container for storing food
- Remove as much paint as possible from brushes and rollers before cleaning
- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
- Avoid release to the environment. Refer to special instructions/ safety data sheet
- No added lead, Mercury or Chromium compounds

PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application
- Do not apply during wet weather
- Do not over thin or overextend the brush
- Do not use universal stainers or any other colourants
- Stir thoroughly before use
- Tinted paints need a thorough shaking immediately after tinter addition as well as before use

For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control,

we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.

PEARLAC PAINTS

(A Unit of Mereena Group)

Mereena Arcade, Ponevashy Cross Road, Kochi- 682 041, Kerala, India

E-Mail: pearlac@mereena.com

Web: www.mereena.com