

## Technical Data Sheet

### NC SANDING SEALER

---



### PHYSICAL DESCRIPTION

NC Sanding Sealer is based in nitrocellulose. It is specially designed formulation. This fills wood grains, dents perfectly and gives after sanding property with smooth surface of wood for subsequent top coat.

---

### SPECIFICATION

|                           |                         |
|---------------------------|-------------------------|
| Colour                    | Haze white              |
| Gloss                     | Matt                    |
| Dilution                  | NC Thinner-SP 98        |
| Mixing ratio with hardner | NA                      |
| Viscosity in Ford Cup B4  | 40 +/- 5 seconds        |
| Specific Gravity          | 0.95 +/- 0.03           |
| Surface Dry               | 10 Minutes – 15 Minutes |
| Tack Free                 | 30Minutes – 40 Minutes  |
| Hard Dry                  | Max 24 Hours            |
| Application               | Spray, Brush            |

---

### PACKING

210 Litre, 20 Litre, 4 Litre, 1 Litre

---

### STORAGE AND HANDLING

**Precautions:** Highly flammable, all sources of ignition must be eliminated in or near area of use, on burning fumes emitted are toxic. Do not smoke in immediate area. Avoid contact with skin or eyes; wear suitable clothing such as impervious overalls, PVC or neoprene gloves, safety goggles and face mask. Avoid inhalation of spray mist and vapours – use with adequate ventilation and suitable Personal Protection Equipment (PPE).

**Storage:** Store away from excessive heat, vapour accumulation, sparks, flames, or a build up of static electricity. Avoid contact with strong oxidisers

---

## **HEALTH AND SAFETY**

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

---

*For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.*

---

## **DISCLAIMER**

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.

---

**PEARLAC PAINTS**

**(A Unit of Mereena Group)**

**Panorama Arcade, Edappally, Cochin-682 024, Kerala, India**

**E-Mail: [pearlac@mereena.com](mailto:pearlac@mereena.com)**

**Web: [www.pearlacpaints.com](http://www.pearlacpaints.com)**

