

Technical Data Sheet

WOOD PRIMER WHITE



PHYSICAL DESCRIPTION

This primer is specially made for penetration into wood, providing both sealing and filling properties, with maximum adhesion. It forms an ideal substrate for building up long life paint systems for interior or exterior wood. Wood Primer is designed for application as a first coat on joinery and construction timber, wooden vehicle bodies, boats and hardboard, plywood etc. It is equally suitable for patch priming local areas which are to be made good and for previously painted wood which has been stripped, burnt off etc.

SPECIFICATION

Colour	White
Gloss	Matt
Dilution	Enamel Thinner /NC Thinner SP 98
Mixing ratio with hardner	NA
Viscosity in Ford Cup B4	80+/-5 seconds
Specific Gravity	1.2 +/- 0.03
Surface Dry	60 Minutes
Tack Free	4 Hours
Hard Dry	Max 24 Hours
Application	Spray, Brush

PACKING

20 Litre, 4 Litre, 1 Litre

STORAGE AND HANDLING

Precautions: Highly flammable, all sources of ignition must be eliminated in or near area of use, on burning fumes emitted are toxic. Do not smoke in immediate area. Avoid contact with skin or eyes; wear suitable clothing such as impervious overalls, PVC or neoprene gloves, safety goggles and face

mask. Avoid inhalation of spray mist and vapours – use with adequate ventilation and suitable Personal Protection Equipment (PPE).

Storage: Store away from excessive heat, vapour accumulation, sparks, flames, or a build up of static electricity. Avoid contact with strong oxidisers

HEALTH AND SAFETY

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.

PEARLAC PAINTS

(A Unit of Mereena Group)

Panorama Arcade, Edappally, Cochin-682 024, Kerala, India

E-Mail: pearlac@mereena.com

Web: www.pearlacpaints.com

