

Technical Data Sheet

NC PUTTY



PHYSICAL DESCRIPTION

It is a special glazing putty for wooden and steel surfaces. Specifically developed, based on nitrocellulose, alkyd resins and extender combinations. Easy to apply, faster drying, suitable for wooden and metal surfaces. Putty for wooden surfaces for better leveling for wooden furniture and carpentry works. Also suitable as a body filler for automotive surfaces.

SPECIFICATION

Colour	Grey
Gloss	Matt
Dilution (If Required)	NC Thinner SP 98
Specific Gravity	1.4 +/- 0.03
Surface Dry	15 – 30 Minutes
Tack Free	60 Minutes
Hard Dry	12Hours
Application	Putty Knife

PACKING

1 KG, 5 KG

STORAGE AND HANDLING

Precautions: Highly flammable, all sources of ignition must be eliminated in or near area of use, on burning fumes emitted are toxic. Do not smoke in immediate area. Avoid contact with skin or eyes; wear suitable clothing such as impervious overalls, PVC or neoprene gloves, safety goggles and face mask. Avoid inhalation of spray mist and vapours – use with adequate ventilation and suitable Personal Protection Equipment (PPE).

Storage: Store away from excessive heat, vapour accumulation, sparks, flames, or a build up of static electricity. Avoid contact with strong oxidisers

HEALTH AND SAFETY

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.

PEARLAC PAINTS

(A Unit of Mereena Group)

Panorama Arcade, Edappally, Cochin-682 024, Kerala, India

E-Mail: pearlac@mereena.com

Web: www.pearlacpaints.com