PEARLAC PAINTS



SAFETY DATA SHEET

1. Identification of the preparation and company

1.1. Product identifier

PS White

1.2. Relevant identified uses of the substance or mixture and uses advised

against Intended; Use Paints and Coatings

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq Flammable liquid and vapor.

Skin Irrit. Causes skin irritation.

Eye Irrit Causes serious eye irritation.

Skin Sens. May cause an allergic skin reaction.

Aquatic Chronic Toxic to aquatic life with long lasting effects.

2.2. Label elements

Flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

Keep away from heat / sparks / open flames / hot surfaces

- No smoking Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapours / spray.

Wash area of contact thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

3. First aid measures

3.1 Description of first aid measures

General Remove contaminated clothing and shoes. Get medical attention immediately. Wash

clothing before reuse. Thoroughly clean or destroy contaminated shoes.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention immediately.

PEARLAC PAINTS



Eyes In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get medical

attention immediately.

Ingestion If swallowed, immediately contact the Poison Control Centre. DO NOT induce

vomiting unless instructed to do so by medical personnel. Never give anything by

mouth to an unconscious person.

Overview NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be

harmful or fatal. Avoid contact with eyes, skin and clothing.

Inhalation Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or

nervous system causing dizziness, headache or nausea.

Eyes Causes severe eye irritation. Avoid contact with eyes.

Skin Causes skin irritation. May be harmful if absorbed through the skin.

Ingestion Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea,

4. Fire-fighting measures

4.1 Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective. SMALL FIRES: Use dry chemical, CO2, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

- 4.2 Special hazards arising from the substance or mixture No data available
- 4.3 Advice for fire-fighters

5. Accidental release measures

5.1 Personal precautions, protective equipment and emergency procedures No action shall be taken involving any personal risk or without suitabletraining.
Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is Inadequate

5.2 Environmental precautions

Do not allow spills to enter drains or watercourses.

5.3 Methods and material for containment and cleaning up

6. Handling and storage

PEARLAC PAINTS



6.1 . Precautions for safe handling

Keep away from heat, sparks and flame.

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discared after each use.

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

6.2 Conditions for safe storage, including any incompatibilities.

Avoid contact with eyes, skin and clothing. Incompatible materials: Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors

7. Exposure controls

7.1 Exposure controls

Respiratory Select equipment to provide protection from the ingredients listed in Section 3 of this

document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's

directions for respirator use.

Eyes Avoid contact with eyes. Safety eyewear complying with an approved standard

should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of

protection: chemical splash goggles.

Skin Chemical-resistant, impervious gloves complying with an approved standard should

be worn at all times when handling chemical products. When there is a risk of ignition from static electricity, wear antistatic protective clothing and footwear. Any additional personal protective equipment or measures should be selected based on the risk assessment of the task being performed and should be approved by a specialist

before handling this product.

Engineering Controls Depending on the site-specific conditions of use, provide adequate ventilation.

immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of

soap and water.



PE8/th) scal and the mical Doparties NTS

Appearance Coloured Liquid
Odour threshold Not Measured

pH No Established Limit
Melting point / freezing point Not Measured
Initial boiling point and boiling range 139 (°C) 282 (°F)
Flash Point 47 (°C) 117 (°F)

9. Stability and reactivity

9.1 Reactivity No

data available

9.2 Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

9.3 Possibility of hazardous reactions

No data available

9.4 Conditions to avoid

No data available

9.5 Incompatible materials

Strong oxidizing agents

Hazardous decomposition products No data available

10. Ecological information

11.1 Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

11.2 Persistence and degradability

No data available

11.3 Bioaccumulative potential

Not Measured

11.4 Mobility in soil

No data available

11.5 Other adverse effects

No data available

12. Disposal considerations

12.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and, regulations

DISCLAIMER The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.

PEARLAC PAINTS

